

Material Safety Data Sheet

BTTRI GAS R403B

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME:

BTTRI GAS R403B

DISTRIBUTOR:

AG CHEM

23 Kolot Beak ST,

Cairo, Egypt

FOR MORE INFORMATION CALL:

IN CASE OF EMERGENCY CALL: 002-011-45-50-95-21

(saturday-thursday,9:00am-5:00pm)

002-0100-12-111-22

2. COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENT NAME	CAS NUMBER	WEIGHT %
Chlorodifluoromethane	75-45-6	55
Perfluoropropane	76-19-7	39
Propane	74-98-6	6

Trace impurities and additional material names not listed above may also appear in Section 15 toward the end of the MSDS. These materials may be listed for local "Right-To-Know" compliance and for other reasons.

3. HAZARDS IDENTIFICATION

POTENTIAL HEALTH HAZARDS

Inhaling high concentrations of vapor is harmful and may cause light-headedness, shortness of breath, heart irregularities, unconsciousness or death. Vapor is heavier than air and may reduce oxygen available for breathing.

Intentional misuse can be fatal.

Human health effects from overexposure by inhalation, ingestion, or skin or eye contact may initially include: temporary nervous system depression with anaesthetic effects such as dizziness, headache, confusion, incoordination and loss of consciousness. Higher exposures may lead to temporary alteration of the heart's electrical activity with irregular pulse, palpitations or inadequate circulation. Gross overexposure may be fatal. Skin contact with liquid may cause frostbite.

Individuals with preexisting diseases of the central nervous system or cardiovascular system may have increased susceptibility

to the toxicity of excessive exposures.

Inhalation 4 hr. LC50: Not established for mixture Oral LD50: Not established for mixture

MSDS: R-403B Page 1 of 5 Current Issue Date: October, 2011



CARCINOGENICITY

Not listed as a carcinogen by IARC, NTP, OSHA or ACGIH.

EXPOSURE LIMITS

PEL (OSHA): 1000 ppm for chlorodifluoromethane and propane

TLV (ACGIH): 1000 ppm for chlorodifluoromethane, 2500 ppm for propane

Perfluoropropane: Not Available

SAFETY PRECAUTIONS

Avoid breathing vapors and prolonged skin exposure. Use with sufficient ventilation to keep exposure below recommended limits.

4. FIRST AID MEASURES

SKIN: Promptly flush skin with plenty of water. Get medical attention if symptoms persist.

EYES: Immediately flush eyes with large amounts of water. Get medical attention if symptoms persist.

INHALATION: Immediately remove to fresh air; keep calm. If breathing is difficult, give oxygen. If breathing has stopped, give artificial respiration. Get medical attention. Do not give epinephrine (adrenaline).

INGESTION: Ingestion is unlikely because of the physical properties and is not expected to be hazardous. Do not induce

vomiting. Call a physician.

ADVICE TO PHYSICIAN: Because of the possible disturbances of cardiac rhythm, catecholamine drugs, such as

epinephrine, should be used with special caution and only in situations of emergency life support.

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES

FLASH POINT: Gas, not applicable per DOT regulations

AUTOIGNITION TEMPERATURE:

UPPER FLAME LIMIT (volume % in air):

LOWER FLAME LIMIT (volume % in air):

AUTODECOMPOSITION TEMPERTURE:

OSHA FLAMMABILITY CLASS:

Not determined
Not determined
Not applicable

EXTINGUISHING MEDIA:

Use extinguishing media as appropriate for combustibles

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Use water spray or fog to cool containers. Cylinders may rupture under fire conditions. Decomposition may occur.

SPECIAL FIRE FIGHTING PRECAUTIONS/INSTRUCTIONS:

Self-contained breathing apparatus (SCBA) is required if cylinders rupture and contents are released under fire conditions.

MSDS: R-403B Page 2 of 5



6. ACCIDENTAL RELEASE MEASURES

IN CASE OF SPILL OR OTHER RELEASE:

Ventilate area. Use self-contained breathing apparatus (SCBA) in case of large spills. Comply with Federal, State and local regulations on reporting releases.

Spills and releases may have to be reported to Federal and/or local authorities. See Section 15 regarding reporting requirements.

7. EXPOSURE CONTROLS / PERSONAL PROTECTION

GENERAL CONTROL MEASURES:

Normal ventilation for standard manufacturing procedures is generally adequate. Local exhaust should be used when large amounts are released. Mechanical (general) ventilation should be used in low places.

PERSONAL PROTECTIVE EQUIPMENT

Butyl gloves should be worn to avoid prolonged or repeated exposure. Chemical splash goggles should be worn as needed to prevent eye contact. Under normal use, no respiratory protection is required when using this chemical. Self-contained breathing apparatus (SCBA) is required if a large spill or release occurs.

8. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Clear, colorless liquid and vapor PHYSICAL STATE: Gas at ambient temperatures

CHEMICAL FORMULA: $CHC1F_2$, C_3F_8 , C_3H_8

ODOR: Slight ethereal

SOLUBILITY IN WATER (weight %): 0.3% wt. @ 77°F (25°C) pH: Neutral

BOILING POINT: -57.1°F (-46.5°C)

VAPOR PRESSURE: 191.2 psia @ 77°F (25°C) VAPOR DENSITY (air = 1.0): 2.7593 lb/ft³ @ 77°F (25°C)

EVAPORATION RATE: >1 **COMPARED TO:** $CC1_4 = 1$

% VOLATILES: 100

LIQUID DENSITY: 71.79 lb/ft³ @ 77°F (25°C)

FLASH POINT: Not applicable

9. STABILITY AND REACTIVITY

NORMALLY STABLE? (CONDITIONS TO AVOID):

The material is stable.

Avoid open flames and high temperatures.

DECOMPOSITION

This material may decompose if exposed to high temperatures (open flames, glowing metal surfaces, etc.) forming hydrochloric and hydrofluoric acids, and possible carbonyl halides.

MSDS: R-403B Page 3 of 5





INCOMPATIBILITIES:

Alkali or alkaline earth metals (powdered Al, Zn, Be, etc)

POLYMERIZATION:

Will not occur.

10. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Comply with Federal, State and local regulations. Do not vent to atmosphere.

11. ENVIRONMENTAL INFORMATION

PRODUCT WARNING LABEL

WARNING: Contains HCFC 22, a substance which harms public health and environment by destroying ozone in the upper atmosphere.

OZONE DEPLETING POTENTIAL

0.05

12. TRANSPORT INFORMATION

US DOT PROPER SHIPPING NAME: Refrigerant Gases, N.O.S. (Chlorodifluoromethane, Perfluoropropane, and Propane)

US DOT HAZARD CLASS: 2.2

US DOT PACKING GROUP: Not applicable US DOT ID NUMBER: UN1078

DOT PLACARD: NON-FLAMMABLE GAS

For additional information on shipping regulations affecting this material, contact the information number found in Section 1.

13. REGULATORY INFORMATION

TOXIC SUBSTANCES CONTROL ACT (TSCA)

TSCA INVENTORY STATUS: Reported/Included

OTHER TSCA ISSUES: None

SARA TITLE III / CERCLA

"Reportable Quantities" (RQs) and/or "Threshold Planning Quantities" (TPQs) exist for the following ingredients.

INGREDIENT NAME

SARA / CERCLA RQ (lb.)

SARA EHS TPQ (lb.)

No ingredients listed in this section

Spills or releases resulting in the loss of any ingredient at or above its RQ requires immediate notification to the National Response Center [(800) 424-8802] and to your Local Emergency Planning Committee.

MSDS: R-403B Page 4 of 5





SECTION 311 HAZARD CLASS:

IMMEDIATE PRESSURE

SARA 313 TOXIC CHEMICALS:

The following ingredients are SARA 313 "Toxic Chemicals". CAS numbers and weight percents are found in Section 2.

INGREDIENT NAME
Chlorodifluoromethane

CAS. NO. 75-45-6 WT% 55%

14. OTHER INFORMATION

OTHER INFORMATION: HMIS Classification: Health – 1, Flammability – 0, Reactivity – 1

NFPA Classification: Health - 1, Flammability - 0, Reactivity - 1

15. DISCLAIMER

National Refrigerants, Inc. believes that the information and recommendations contained herein (including data and statements) are accurate as of the date hereof. NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY, OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated and may not be valid where such product is used in combination with any other methods or use of the product and of the information referred to herein are beyond the control of National Refrigerants. National Refrigerants expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.

MSDS: R-403B Page 5 of 5